

# MODEL:CT-1A

## CT-1A ALUMINUM GANTRY CRANE

Rated load (ton)	Total height (mm)	Max lifting height (mm)	Outside Span (mm)	Inner Span (mm)	H, Height (mm)
0.5t	3000	2420	2000	1880	460
0.5t	3000	2420	3000	2880	460
0.5t	4000	3420	3000	2880	460
0.5t	4000	3420	4000	3880	460
1.0t	3000	2470	2000	1880	410
1.0t	3000	2470	3000	2880	410
1.0t	4000	3470	3000	2880	410
1.0t	4000	3470	4000	3880	410
2.0t	3000	2215	2000	1800	535
2.0t	3000	2215	3000	2800	535
2.0t	4000	3215	3000	2800	535
2.0t	4000	3215	4000	3800	535
3.0t	3000	2122	2000	1800	685
3.0t	3000	2122	3000	2800	685
3.0t	4000	3122	3000	2800	685
3.0t	4000	3122	4000	3800	685



### FEATURES

- Durable, lightweight and stable
- Extremely portable and allow you to easily move them from one area to another
- Corrosion resistance. Aluminium does not corrode so it is as perfect material for controlled environment
- Easy assembly. It can assembled and disassembled easily by individual
- Simple and easy to use.

### DESIGN STANDARDS

- Design standards in accordance to EN ISO 12100:2010; EN 60204-1:2018