

# MODEL:CT-2A

## CT-2A ALUMINUM GANTRY CRANE

Rated load (ton)	Total height (mm)	Max lifting height (mm)	Outside Span (mm)	Inner Span (mm)	H, Height (mm)
1.0t	2000~3000	2470	3000	2880	410
1.0t	2000~3000	2470	4000	3880	410
1.0t	2600~4000	3470	3000	2880	410
1.0t	2600~4000	3470	4000	3880	410
2.0t	2000~3000	2215	3000	2800	535
2.0t	2000~3000	2215	4000	3800	535
2.0t	2600~4000	3315	3000	2800	535
2.0t	2600~4000	3315	4000	3800	535
3.0t	2000~3000	2122	3000	2800	685
3.0t	2000~3000	2122	4000	3800	685
3.0t	2600~4000	3122	3000	2800	685
3.0t	2600~4000	3122	4000	3800	685



### FEATURES

- Durable, lightweight and stable
- Extremely portable and allow you to easily move them from one area to another
- Corrosion resistance. Aluminium does not corrode so it is as perfect material for controlled environment
- Easy assembly. It can assembled and disassembled easily by individual
- Simple and easy to use.

### DESIGN STANDARDS

- Design standards in accordance to EN ISO 12100:2010; EN 60204-1:2018