

CT-3A ALUMINUM GANTRY CRANE

MODEL:CT-3A

| Rated load (ton) | Total height (mm) | Max lifting height (mm) | Outside Span (mm) | Inner Span (mm) | H, Height (mm) |
|------------------|-------------------|-------------------------|-------------------|-----------------|----------------|
| 1.0t | 2000~3000 | 2470 | 3000 | 2880 | 410 |
| 1.0t | 2000~3000 | 2470 | 4000 | 3880 | 410 |
| 1.0t | 2600~4000 | 3470 | 3000 | 2880 | 410 |
| 1.0t | 2600~4000 | 3470 | 4000 | 3880 | 410 |
| 2.0t | 2000~3000 | 2215 | 3000 | 2800 | 535 |
| 2.0t | 2000~3000 | 2215 | 4000 | 3800 | 535 |
| 2.0t | 2600~4000 | 3315 | 3000 | 2800 | 535 |
| 2.0t | 2600~4000 | 3315 | 4000 | 3800 | 535 |
| 3.0t | 2000~3000 | 2122 | 3000 | 2800 | 685 |
| 3.0t | 2000~3000 | 2122 | 4000 | 3800 | 685 |
| 3.0t | 2600~4000 | 3122 | 3000 | 2800 | 685 |
| 3.0t | 2600~4000 | 3122 | 4000 | 3800 | 685 |

DESIGN STANDARDS

- Design standards in accordance to EN ISO 12100:2010; EN 60204-1:2018



FEATURES

- Durable, lightweight and stable
- Extremely portable and allow you to easily move them from one area to another
- Corrosion resistance. Aluminium does not corrode so it is as perfect material for controlled environment
- Easy assembly. It can assembled and disassembled easily by individual
- Simple and easy to use.